


Sleeves

BOOK INDEX

SECTION INDEX

37° flare adapters used in conjunction with ISO 8434-1 / DIN 2353 fitting bodies

Port to W DIN 3861



Series	Pressure PN	Tube O.D. D1 + Tol.	L2	Part code
L	500	6	10.5	DR-06-L
L	500	8	11.0	DR-08-L
L	500	10	12.5	DR-10-L
L	400	12	13.0	DR-12-L
L	400	15	14.0	DR-15-L
L	400	18	14.5	DR-18-L
L	315	22	18.0	DR-22-L
L	250	28	17.0	DR-28-L
L	250	35	19.0	DR-35-L
L	250	42	21.0	DR-42-L

Series	Pressure PN	Tube O.D. D1 + Tol.	L2	Part code
S	800	6	10.5	DR-06-S
S	800	8	11.0	DR-08-S
S	800	10	12.5	DR-10-S
S	630	12	13.0	DR-12-S
S	630	14	14.5	DR-14-S
S	630	16	17.0	DR-16-S
S	420	20	17.5	DR-20-S
S	420	25	20.0	DR-25-S
S	420	30	21.5	DR-30-S
S	420 (1)	38	26.5	DR-38-S

(1) In the 420 bar section, the normal safety factor of 4:1 is reduced to 3:1.